

PRO-TEC PREMIUM ATF 6 MVLV

Description/Application/Properties

ATF 6 is a low-viscosity automatic transmission oil which is based on an outstanding additive technology. It has excellent corrosion and rust protection properties, stable oxidation behavior and low foaming. This lubricant has been developed to meet the needs of modern transmission where higher efficiency is required.

ATF 6 is recommended for use in the latest generation of high efficiency 6-speed automatic transmissions with longer fluid life capabilities and heavier load capacities.

Customer Benefits

Excellent viscosity stability in operation, Exceptional friction and anti-shudder performances. Fuel economy, Outstanding film-strength and anti-wear properties, Enhanced thermal stability and oxidation resistance, Very good foaming control, Excellent parts material compatibility

Specification/Recommendation

Meets The Requirements of:

DEXRON VI, Daimler / Mercedes MB236.41, 236.14, 236.12, Aisin Warner AW-1, Aisin Warner AW F8FXX, Aisin Warner JWS 3324, Bentley P/N PY112995PA, BMW/Mini P/N 83 22 0 142 516, BMW/Mini P/N 83 22 0 397 114, BMW/Mini P/N 83 22 2 163 514 (BMW 8072 B), Chrysler/Dodge/Jeep P/N 05127382AA, Chrysler/Dodge/Jeep P/N 68043742AA, FORD/Lincoln/Mercury P/N XT-10-QLV [LV], FORD/Lincoln/Mercury P/N XT-6-QSP or -DSP [SP], GM/GMC/Opel/Saturn AW1, GM/GMC/Opel/Saturn P/N 88863400, 88863401, Honda/Acura DW-1, Honda 082000-9017 (ATF Type 3.1), Hyundai/Kia NWS-9638 T-5, Hyundai/Kia P/N 040000C90SG, Hyundai/Kia SP-IV / SPH-IV, Jaguar Fluid 8432, JASO M315, Class 1A, Land Rover P/N TYK500050, LR0022460, Maserati P/N 231603, Mazda FW 6A EL, FW 6AX EL, Mazda FZ, Mercon LV, Mitsubishi ATF-J3, Mitsubishi SP-IV, Nissan/Infinity Matic-S, Porsche P/N 000 043 304 00, Saab P/N 93 165 147 - AW-1, Shell 3353, Shell 134, Shell 1375.4, Toyota/Lexus/Scion WS, VW/Audi G 052 533, G 055 005 (-A, A2), VW/Audi G 055 540 (A2)

| TEST | UNIT | TEST METHOD | RESULT |
|--------------------|--------------------|-------------|--------|
| COLOR | - | - | RED |
| DENSITY AT 15°C | kg/m ³ | ASTM D 4052 | 843 |
| VISCOSITY AT 40°C | mm ² /s | ASTM D 445 | 27.1 |
| VISCOSITY AT 100°C | mm ² /s | ASTM D 445 | 5.6 |
| VISCOSITY INDEX | - | ASTM D 2270 | 150 |
| FLASH POINT | °C | ASTM D 92 | 226 |
| POUR POINT | °C | ASTM D 97 | -45 |

Unsere technischen Informationen stützen sich auf sorgfältige Untersuchungen und wurden nach dem neuesten Stand zusammengestellt. Dennoch kann sie nur unverbindlich beraten, da Anwendung und Verarbeitungsmethoden nicht in unserem Einfluss liegen. Keine Haftung für Druckfehler. Technische Änderungen vorbehalten.
Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.

