

PRO-TEC PREMIUM ATF 3

Description/Application/Properties

ATF 3 is used in automatic transmissions, power steering systems, fluid couplings, hydrodynamic converters and hydraulics in cars, trucks, buses and construction vehicles where manufacturer`s specifications require an ATF Type Dexron III H.

Customer Benefits

High anti oxidation capacity, thermal stability and detergent properties, High viscosity index, Excellent wear protection of gears, pumps and thrust bearings, Excellent anticorrosion and antirust properties .

Specification/Recommendation

Meets The Requirements of:

DEXRON III H und Dexron III G, MB 236.7, 236.6, 236.5 & 236.1 , Allison C-4, Allison TES, 389, MAN 339 Typ Z1 & V1, Z2 & V2, Ford Mercon, Ford M2C138-CJ, M2C 166-H, Volvo 97340, 97341, Voith 55.6335 & 55.6336, ZF TE-ML 02F, 04D, 09,11A, 14A & 17C

TEST	UNIT	TEST METHOD	RESULT
COLOR	-	-	RED
DENSITY AT 15°C	kg/m ³	ASTM D 4052	846
VISCOSITY AT 40°C	mm ² /s	ASTM D 445	39.4
VISCOSITY AT 100°C	mm ² /s	ASTM D 445	7.9
VISCOSITY INDEX	-	ASTM D 2270	182
FLASH POINT	°C	ASTM D 92	226
POUR POINT	°C	ASTM D 97	-50

Unsere technischen Informationen stützen sich auf sorgfältige Untersuchungen und wurden nach dem neuesten Stand zusammengestellt. Dennoch kann sie nur unverbindlich beraten, da Anwendung und Verarbeitungsmethoden nicht in unserem Einfluss liegen. Keine Haftung für Druckfehler. Technische Änderungen vorbehalten.
Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.

