

PRO-TEC PREMIUM SL 10W-40

Description/Application/Properties

SAE 10W-40 is a semi-synthetic engine oil for all vehicles with petrol and diesel engines with or without turbochargers. Due to the high viscosity range the oil is ideal for all-season use. SAE 10 W40 is perfectly suited to normal driving conditions.

Customer Benefits

Manufacturers standards, Resistance to oxidation, Engine protection and cleanliness, Long-term wear Protection and increasing engine life.

Specification/Recommendation

Meets The Requirements of:

API SL/CF, ACEA A3/B4-10

MB 229.1, PSA B71 2294, Renault RN 700/710, VW 501 01/505 00

Recommended for previous vehicles engines technology:

Peugeot, Toyota, Hyundai and Kia

TEST	UNIT	TEST METHOD	RESULT
VISCOSITY GRADE	-	SAE 300	10 W 40
DENSITY AT 15°C	kg/m ³	ASTM D 4052	867.5
VISCOSITY AT 40°C	mm ² /s	ASTM D 445	95.01
VISCOSITY AT 100°C	mm ² /s	ASTM D 445	14.4
VISCOSITY INDEX	-	ASTM D 2270	157
FLASH POINT	°C	ASTM D 92	225
POUR POINT	°C	ASTM D 97	-33

Unsere technischen Informationen stützen sich auf sorgfältige Untersuchungen und wurden nach dem neuesten Stand zusammengestellt. Dennoch kann sie nur unverbindlich beraten, da Anwendung und Verarbeitungsmethoden nicht in unserem Einfluss liegen. Keine Haftung für Druckfehler. Technische Änderungen vorbehalten.
Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.

