

PRO-TEC PREMIUM SN 5W-40

Description/Application/Properties

SAE 5W-40 is a fully synthetic modern high-performance engine oil with reduced ash content, specially formulated to meet the requirements of VW for universal usage and in particular compatible with diesel particulate filter (DPF).

SAE 5W-40 guarantees excellent wear protection and offers durable and stable performance level for the requirements of extended oil change intervals. Fuel saving and environmental protection also with FSI engines and diesel engines with or without DPF and turbocharger.

Customer Benefits

Anti wear protection, Oxidation resistance, Engine protection,
Cleanliness and Performance, easier cold starts and Fluidity

Specification/Recommendation

Meets The Requirements of:

API SN/CF, ACEA A3/B4-16

MB 229.5/226.5, BMW LL04/LL01/LL98, Fiat 9.55535-S2, Renault RN710/700, VW 502 00/ 505 00,
Ford WSS-M2C917-A, Porsche A40, Opel GM-LL-B-025, PSA B71 2296

Recommended for: Peugeot, Toyota, Hyundai and Kia

TEST	UNIT	TEST METHOD	RESULT
VISCOSITY GRADE	-	SAE 300	5 W 40
DENSITY AT 15°C	kg/m ³	ASTM D 4052	855
VISCOSITY AT 40°C	mm ² /s	ASTM D 445	85
VISCOSITY AT 100°C	mm ² /s	ASTM D 445	14.4
VISCOSITY INDEX	-	ASTM D 2270	171
FLASH POINT	°C	ASTM D 97	238
POUR POINT	°C	ASTM D 92	-36

Unsere technischen Informationen stützen sich auf sorgfältige Untersuchungen und wurden nach dem neuesten Stand zusammengestellt. Dennoch kann sie nur unverbindlich beraten, da Anwendung und Verarbeitungsmethoden nicht in unserem Einfluss liegen. Keine Haftung für Druckfehler. Technische Änderungen vorbehalten.

Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.