

PRO-TEC PREMIUM SN 10W-40

Description/Application/Properties

SAE 10W-40 is a fully synthetic engine oil for all vehicles with petrol and diesel engines with or without turbocharger. Due to the high viscosity range the oil is ideal for all-season use.

SN 10W-40 is perfectly suited to normal driving conditions.

Customer Benefits

Manufacturers standards, Resistance to oxidation, Engine protection and cleanliness, Long-term wear protection and increasing engine life.

Specification/Recommendation

Meets The Requirements of:

API SN/CF, ACEA A3/B4-12

MB 229.3 (deckt MB 229.1 ab), PSA B71-2300,

Renault RN 710/700, VW 502 00 / 505 00,

FIAT 9.55535 - G2/D2

Recommended for: Peugeot, Toyota, Hyundai and Kia

TEST	UNIT	TEST METHOD	RESULT
VISCOSITY GRADE	-	SAE 300	10W40
DENSITY AT 15°C	kg/m ³	ASTM D 4052	856.2
VISCOSITY AT 40°C	mm ² /s	ASTM D 445	94.1
VISCOSITY AT 100°C	mm ² /s	ASTM D 445	14.7
VISCOSITY INDEX	-	ASTM D 2270	165
FLASH POINT	°C	ASTM D 92	242
POUR POINT	°C	ASTM D 97	-39

Unsere technischen Informationen stützen sich auf sorgfältige Untersuchungen und wurden nach dem neuesten Stand zusammengestellt. Dennoch kann sie nur unverbindlich beraten, da Anwendung und Verarbeitungsmethoden nicht in unserem Einfluss liegen. Keine Haftung für Druckfehler. Technische Änderungen vorbehalten.

Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.

