

## PRO-TEC PREMIUM PROMOTO MOTORCYCLE 10W-40 SL

### Description/Application/Properties

MOTORCYCLE 10W-40 SL is a synthetic based lubricant that is particularly recommended for all types of 4-stroke engine motorcycles, in compliance with the API SL and JASO MA2 international standards.

MOTORCYCLE 10W-40 SL is perfectly compatible with catalytic converters. The oil -change intervals recommended by the constructor and the minimum required viscosities must be complied with.

MOTORCYCLE 10W-40 SL has a specific reactivity to temperature variations. Its maximum fluidity at low temperatures improves injection and ensures that oil pressures rise quickly.

### Customer Benefits

Oxidation resistance .

Viscosity controlled in relation to temperature.

Piston ring sealing ,power gain.

Anti clutch slippage.

### Specification/Recommendation

Meets The Requirements of:

API SL

JASO MA2

Recommended for: Honda, Yamaha, Suzuki, Kawasaki, Benelli

TEST	UNIT	TEST METHOD	RESULT
VISCOSITY GRADE	-	SAE 300	10W40
DENSITY AT 15°C	kg/m <sup>3</sup>	ASTM D 4052	870
VISCOSITY AT 40°C	mm <sup>2</sup> /s	ASTM D 445	97.6
VISCOSITY AT 100°C	mm <sup>2</sup> /s	ASTM D 445	14.2
VISCOSITY INDEX	-	ASTM D 2270	153
FLASH POINT	°C	ASTM D 92	225
POUR POINT	°C	ASTM D 97	-30

Unsere technischen Informationen stützen sich auf sorgfältige Untersuchungen und wurden nach dem neuesten Stand zusammengestellt. Dennoch kann sie nur unverbindlich beraten, da Anwendung und Verarbeitungsmethoden nicht in unserem Einfluss liegen. Keine Haftung für Druckfehler. Technische Änderungen vorbehalten.  
Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.