



PRO-TEC PREMIUM PROMOTO MOTORCYCLE 10W-60 SN 100% SYNTHETIC (PAO /ESTER)

Description/Application/Properties

MOTORCYCLE 10W-60 SN is a 100% synthetic lubricant with PAO that is particularly recommended for all types of high performance 4-stroke engine motorcycle, in compliance with the API SN and JASO MA2 international standards.

MOTORCYCLE 10W-60 SN, advanced full synthetic motor oil is made with a proprietary blend of ultra high performance synthetic base stocks fortified with a precisely balanced component system. MOTORCYCLE 10W-60 SN, meets the requirements of 4-stroke catalytic converters.

The manufacturer's recommended oil change intervals and the required minimum viscosities must be complied with.

MOTORCYCLE 10W-60 SN, its viscosity increases the resistance of the oil film to extreme variations in temperature.

Customer Benefits

Engine cleanliness, maintains power.

Viscosity controlled in relation to temperature.

Stability at high temperatures.

Synergy of Ester with anti-wear additives and improved shear resistance for improved gear protection and life time.

Extra seal conditioners to help prevent oil leaks.

Specification/Recommendation

Meets The Requirements of:

API SN JASO MA2

Recommended for: Honda, Yamaha, Suzuki, Kawasaki, Benelli

TEST	UNIT	TEST METHOD	RESULT
VISCOSITY GRADE	ı	SAE 300	10W60
DENSITY AT 15°C	kg/m³	ASTM D 4052	854
VISCOSITY AT 40°C	mm²/s	ASTM D 445	173
VISCOSITY AT 100°C	mm²/s	ASTM D 445	23.9
VISCOSITY INDEX	ı	ASTM D 2270	170
FLASH POINT	°C	ASTM D 92	248
POUR POINT	°C	ASTM D 97	-33

Unsere technischen Informationen stützen sich auf sorgfältige Untersuchungen und wurden nach dem neuesten Stand zusammengestellt. Dennoch kann sie nur unverbindlich beraten, da Anwendung und Verarbeitungsmethoden nicht in unserem Einfluss liegen. Keine Haftung für Druckfehler. Technische Änderungen vorbehalten. Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.

