

PRO-TEC PREMIUM PROMOTO MOTORCYCLE 10W-30 SN MB

Description/Application/Properties

MOTORCYCLE 10W-30 SN is a fully synthetic motorcycle oil specially designed to meet today's 4-Stroke scooter specifications where JASO MB specification is required. JASO MB lubricant ensures optimal engine performance and fuel economy on all scooters without wet clutch.

MOTORCYCLE 10W-30 SN is developed in view with the modern riding conditions and to ensure optimum performance of the engine even at extreme conditions. Its special additive technology improves the hydrodynamic lubrication, controlling friction and minimizing wear and abrasion. Provides better lubricity – Reduces wear and keeps the engine strong. Its unique detergency gives better cleaning, prolongs engine life.

Customer Benefits

- Full synthetic base oil helps maintain oils initial conditions thanks to good stability and high viscosity index

- Base Oil's good quality provides long engine life and low costs for maintenance (but manufacturers recommended oil change intervals must be complied with)

Excellent engine and major parts lubrication and protection in all severe condition including normal daily urban or rural traffic (long trips and short commuting under stop-and-go conditions)

- Lower friction factor proved by official friction test gives good transmission performance and fuel economy improvement

Specification/Recommendation

Meets The Requirements of:

API SN/CF JASO MB Recommended for: Honda, Yamaha, Suzuki, Kawasaki and SYM

TEST	UNIT	TEST METHOD	RESULT
VISCOSITY GRADE	-	SAE 300	10W30
DENSITY AT 15°C	kg/m³	ASTM D 4052	850
VISCOSITY AT 40°C	mm²/s	ASTM D 445	65.80
VISCOSITY AT 100°C	mm²/s	ASTM D 445	10.70
VISCOSITY INDEX	-	ASTM D 2270	154
FLASH POINT	°C	ASTM D 92	230
POUR POINT	°C	ASTM D 97	-36

Unsere technischen Informationen stützen sich auf sorgfältige Untersuchungen und wurden nach dem neuesten Stand zusammengestellt. Dennoch kann sie nur unverbindlich beraten, da Anwendung und Verarbeitungsmethoden nicht in unserem Einfluss liegen. Keine Haftung für Druckfehler. Technische Änderungen vorbehalten. Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.

07338 Leutenberg Germany Tel.: +49 (0)36734 230-0 Fax: +49 (0)36734 230-22 www.bluechemgroup.com www.ctp.de